

partlist Cave-radio	Q	min order Q	value	Farnell	RS	case	price EU pp	page
C 1 2	2	10	100-pF	499 274		1206	0,15	542
C 28 29 40 45	4	5	100-pF	550 371		805	0,49	591
C 36 37 41 42	4	10	150-pF	331 2173		1206	0,19	547
C 27 30 39 44	4	5	330-pF	550 401		805	0,49	591
C 25 26 38 43	4	5	680-pF	550 437		805	0,49	591
C 7	1	10	1-nF	499 328		1206	0,13	542
C 31 46	2	10	2-nF-2	499 330		1206	0,13	542
C 51	1	10	3-nF-3	498 622		1206	0,13	542
C 3 6 9 16	4	10	10-nF	499 353		1206	0,13	542
C 50	1	10	15-nF	331 2987		805	0,13	547
C 32 33 34 47 49 65	6	10	22-nF	499 365		1206	0,19	542
C 11 13 14 18 19 20 21 22 23 24 53 55 61 62 66 67	16	10	100-nF	499 389		1206	0,23	542
C 4 5 8 15 17	5	10	470nF	499 705		1206	0,46	542
C 12 52 54 63	4	10	1-uF	499 717		1206	0,61	542
C 10	1	1	2-uF2	814 039		pitch 5mm	2,16	570
C 35 57	2	5	4-uF-7 (16V)	197 269		Tantaal-B	0,75	593
C 58	1	5	47-uF (10V)	197 166		Tantaal-C	1,76	592
C 56 60	2	5	100uF (10V)	197 180		Tantaal-C	2,44	592
C 59 (64 optional)	2	5	100-uF (16V)	197 348		Tantaal-D	2,83	593
C 48	1	5	150-uF	305 492		Axial	0,67	614
R 8 10	2	50	2-R-2	758 371		1206	0,04	716
R 4	1	50	100-R	912 359		1206	0,04	715
R 107 108 109	3	50	180-R	912 384		1206	0,04	715
R 9 13	2	50	220-R	912 396		1206	0,04	715
R 1	1	50	270-R	912 402		1206	0,04	715
R 11 95	2	50	470-R	912 438		1206	0,04	715
R 54 55 70 71 112	5	50	1-k	912 475		1206	0,04	715
R 29 51 52 62 67 68	6	50	1-K-5	912 499		1206	0,04	715
R 12	1	50	2-K-2	912 517		1206	0,04	715
R 47 49 50 94 100 101	6	50	4-K-7	912 554		1206	0,04	715
R 5 7	2	50	5-K-6	912 566		1206	0,04	715
R 41 43 44 45 84 85 86 89	8	50	6-K-8	912 578		1206	0,04	715
R 40 66 76 90 91	5	50	8-K-2	912 580		1206	0,04	715

R 25 26 39 53 56 57 69 72 73 92 96 107 108 109 111	15	50	10-K	912 591		1206	0,04	715
R 42 87	2	50	13-K	321 8193		805	0,04	715
R 2 3 14 27 38 58 74 78 88	9	50	15-K	912 610		1206	0,04	715
R 36 79	2	50	18-K	912 621		1206	0,04	715
R 37 59 75	3	50	20-K	321 8211		805	0,04	715
R 23 24	2	50	22-K	912 633		1206	0,04	715
R 46	1	50	39-K	912 669		1206	0,04	715
R 17 18 19 20 21 22 46 81 82 83	10	50	47-K	912 670		1206	0,04	715
R 30 61	2	50	56-K	912 682		1206	0,04	715
R 6 15 16 48 97 104 105 106	8	50	100-K	912 712		1206	0,04	715
R 28 77	2	50	110-K	321 8302		805	0,04	715
R 35 80	2	50	180-K	912 748		1206	0,04	715
R 33 34 64 65	4	50	220-K	912 750		1206	0,04	715
R 32 63	2	50	330-K	912 773		1206	0,04	715
R 31 60	2	50	430-K	321 8375		805	0,04	715
R 93 98 102	3	50	470K	912 797		1206	0,04	715
R 99	1	50	1000-K	912 839		1206	0,04	715
RV 3	1	1	5-K	347 980		3296x	2,15	750
RV 1 5	2	1	10-K	347 991		3296x	2,15	750
RV 2	1	1	20-K	348 004		3296X	2,15	750
		10	RED	515 656		SOT23	0,72	426
D 1 2 3 4 5 6 7 8	8	10	LL4148	739 182		MINIMELF	0,09	63
Q 3 4	2	10	BC847C	932 980		SOT23	0,09	7
Q 1 2 5	3	5	2N3819	352 299		TO-92	1,14	52
U 1	1	1	OP37GP	398 123		DIL-8	4,12	271
U 2	1	1	TDA2003	410 573		TO-220	2,53	331
U 3	1	1	CD74HCT4040M	539 570		SOP16-225	1,3	141
U 4	1	1	CD4013BCN	384 616		DIL-14	0,26	147
U 6 15	2	1	KA78L09		298 7145	TO-92	0,43	41
U 14	1	1	KA741D	345 8155		SOP8.225	0,44	273
U 9 10 11 12 13	5	1	TL074	401 389		DIL 14	1,11	281
U 17	1	1	PIC 16F84	794 508		DIL 18	10,07	220

U18	1	1	CD4040BCM	505 274		SOP16.225	0,37	149
U19	1	1	CD4013BCM	505 195		SOP14.225	0,26	149
U 7 8	2	1	CD4053BCN	385 372		DIL16	0,41	148
U 15 (optional)	1	1	TDA7052A	526 198		DIL 8	2,29	333
U 5	1	1	LM78L05	412 430		TO92	0,73	339
Rel 1 2	2	1	5v (178R)	177 225		DIL-10	4,55	669
X 1 (8MHz clock module)	1	1	8 MHz	221 624		DIL-8	1,04	253
L 1 2 3 4	4	10	10uH	200 360		1812	1,06	686
L 5 6 7 8 (TOKO RWO6A6408)	4		360uH					
L9 EFD-20 Halfcore	2	1		200 270			0,99	856
L9 EFD-21 Bobine 8 pin	1	1		200 281			2,08	856
L9 EFD-22 retaining clip	2	1		200 293			0,24	856
FU 1	1	10	3A	975 321		1206	0,33	556
Battery indicator	1				258 833		12,67	570
TX current meter	2				258 849		11,98	570